

Message Templates


Message templates are used mainly in connection with sending e-mails to your clients, prospects or partners.

Message template may be used when sending individual e-mail correspondence. Message template is required when sending Mass Mail. Message template is heavily used when automating processes using Atollon Troll (Workflow) module.

Message Templates Overview


The overview of message templates provides list of **Message Template Containers**. Click on one of the containers to add / view / edit / delete one of the message templates on right.

You can filter only for Message Templates in specific language by selecting one of the languages in the list of languages.



Edit Message Template

To edit the Message Template, double click on one of the items in grid.



Mail Merge Fields

Basic rule for using merge fields:

- \${CAPITAL-LETTERS} - may be used on both client & server side
- \${small-letters} - may be used on client side only

General

`${SALUTATION}` | Enters the string that is found in recipient contact's Salutation field.
`${SIGNATURE}` | Enters user's mailbox identity signature.

Calendar / Tasks Notifications

Main tags

`${NAME}` | Task / Event name
`${DESCRIPTION}` | Task / Event description
`${STATUS}` | Task / Event status
`${START}` | Task / Event start date/time
`${END}` | Task / Event deadline / end date/time
`${CONTEXT}` | Task / Event context

`${TYPEOFWORK}` | Task / Event context

Other tags

`${LOCATION}` | Event location

`${PRIORITY}` | Task priority

`${DURATION}` | Event duration

`${REMAINING}` | Event duration

`${USERS}` | Event participants / Task solver

`${GARANTS}` | Resource garants

`${RESOURCES}` | Resources

Service Level Notifications

`${REQUESTSUBJECT}` | request subject

`${REQUESTDESC}` | request description

`${REQUESTIDENT}` | request id

`${REQUESTSENDER}` | request sender

`${REQUESTPROJECTNAME}` | project & subject (if is known)

`${REQUESTDATETIME}` | request date/time

Message Context Dependent Fields

`${ACTIVITYNAME}`

`${ACTIVITYREFID}`

`${PROJECTNAME}`

`${PROJECTREFID}`

`${MASTERPROJECTNAME}`

`${MASTERPROJECTREFID}`

`${FOLDERNAME}`

`${FOLDERREFID}`

`${CONTEXTREFID}`

Recipient Dependent Fields

```
${RECIPIENT- ID}  
${RECIPIENT- EMAIL}  
${RECIPIENT- FIRSTNAME}  
${RECIPIENT- MIDDLENAME}  
${RECIPIENT- LASTNAME}
```

Invoice Fields

```
${doc_number}  
${doc_descr}  
${doc_total_amount}  
${doc_due_date}
```

Same naming conventions are for all following items (`${word before :}`)

```
doc_number: "invoiceNumber",  
doc_descr: "transactionsName",  
doc_total_amount: "totalWithVAT",  
doc_due_date: "dueDate",  
doc_ccy: "currency",  
doc_ccy_rate: "currencyRate",  
doc_bank_code: "bankCode",  
doc_bank_account: "bankAccount",  
doc_iban: "bankIBAN",  
doc_description: "description",  
doc_header_text: "headerText",  
doc_footer_text: "footerText",  
doc_summary_text: "summaryText",  
doc_period_from: "periodFrom",  
doc_period_to: "periodTo",  
doc_trans_name: "transactionsName"
```

Custom Form

```
${generatedLink}
```

Campaign Planner / Event

```

    ${eventFrom}
    ${eventTo}
    ${eventLocation}
    ${eventUserName}
    ${eventDescription}

```

Folder / Project / Activity (Context items)

```

    ${contextName} -> name
    ${contextReferenceId} -> referenceId
    ${contextComment} -> comment
    ${contextCreated} -> created
    ${contextCreatedBy} -> createdByName
    ${contextModified} -> modified
    ${contextModifiedBy} -> modifiedByName

```

System IDs for message templates in system

SystemId	Description
com.atollon.messaging.issuedinvoicemail	template with message for mail with issued invoice
com.atollon.messaging.invoicereceivedmail	template with message for mail with recieved invoice
com.atollon.messaging.orderissuedmail	template with message for mail with issued order
com.atollon.messaging.orderreceivedmail	template with message for mail with recieved order
com.atollon.messaging.estimatemail	template with message for mail with estimate